



開放型
Open



32 屏蔽型
Shielded



34 接触屏蔽型
Contact Shielded




CE-CEU 接触屏蔽型
Contact Shielded

63300 系列 63300 series

轴承型号 Bearing Number	内径/mm Bore(D)	外径/mm OD(D)	高度/mm Width(B)	基本载荷 KN		重量/kg Weight
				额定动 C	额定静 Co	
63302	15	42	19.0	8.71	5.34	0.150
63303	17	47	22.2	10.42	6.35	0.180
63304	20	52	23.2	12.23	7.62	0.210
63305	25	62	25.4	16.22	10.55	0.250
63306	30	72	30.2	20.44	14.00	0.340
63307	35	82	34.8	25.56	18.00	0.420

(英制 RLS 系列) Inch RLS Series

轴承型号 Bearing Number	内径/mm Bore(D)	外径/mm OD(D)	高度/mm Width(B)	基本载荷 KN		重量/kg Weight
				额定动 C	额定静 Co	
RL54	12.700	33.338	9.525	4.26	2.81	0.038
RL55	15.875	39.668	11.113	6.62	4.81	0.087
RL56	19.050	47.625	14.288	9.08	5.19	0.120
RL57	22.225	50.800	14.288	9.72	6.20	0.142
RL58	28.400	67.150	18.875	10.78	6.86	0.180
RL59	28.575	69.500	19.875	12.60	8.40	0.185
RL510	31.750	69.850	17.462	17.64	13.19	0.285
RL511	34.925	76.200	17.462	18.77	15.20	0.362
RL512	38.100	82.550	18.050	25.06	19.14	0.462
RH54	12.700	41.275	15.875	7.26	4.41	0.1070
RH55	15.875	50.800	18.875	10.46	6.86	0.1170
RH56	19.050	59.800	17.462	9.68	6.20	0.1660
RH57	22.225	67.150	17.462	10.78	6.86	0.220
RH58	28.400	83.800	19.280	17.22	11.28	0.289
RH59	28.575	71.438	20.638	27.00	15.19	0.372
RH510	31.750	79.375	22.225	27.60	15.19	0.542



Inch 1600 Series

轴承型号 Bearing No.	内径 d		外径 D		宽度 B		轴角 Camber Dist.	额定负荷 (kN)			
	mm	in	mm	in	mm	in		静负荷 C ₀ (kN)	动负荷 C _r (kN)		
1601 标准型 Open	4.763	.1875	17.463	.6875	6.35	.25	7.938	.3125	0.30	1670	730
1602 标准型 Open	6.350	.2500	17.463	.6875	6.35	.25	7.938	.3125	0.30	1670	730
1603 标准型 Open	7.938	.3125	22.225	.8750	7.144	.2813	8.731	.3437	0.30	3090	1380
1604 标准型 Open	9.525	.3750	22.225	.8750	7.144	.2813	8.731	.3437	0.30	3090	1410
1605	7.938	.3125	23.017	.9092	7.938	.3125	0.30	3330	1410		
1606	9.525	.3750	23.017	.9092	7.938	.3125	0.30	3330	1410		
1607	11.113	.4375	23.017	.9092	7.938	.3125	0.30	2650	1270		
1614	9.525	.3750	28.575	1.125	9.525	.375	0.64	9110	2390		
1615	11.113	.4375	28.575	1.125	9.525	.375	0.64	9110	2390		
1616	12.700	.5000	28.575	1.125	9.525	.375	0.64	9110	2390		
1620	11.113	.4375	34.925	1.375	11.102	.4375	0.64	7450	3700		
1621	12.700	.5000	34.925	1.375	11.102	.4375	0.64	7450	3700		
1622	14.288	.5625	34.925	1.375	11.102	.4375	0.64	7450	3700		
1623	15.875	.6250	34.925	1.375	11.102	.4375	0.64	7450	3700		
1626	15.875	.6250	41.275	1.625	12.7	.5000	0.64	9390	5000		
1630	18.000	.7000	41.275	1.625	12.7	.5000	0.64	9390	5000		
1633	15.875	.6250	44.480	1.750	12.7	.5000	0.64	9390	5000		
1636	18.000	.7000	44.480	1.750	12.7	.5000	0.64	9390	5000		
1638	18.000	.7000	53.680	2.1	14.288	.5625	0.64	10000	5880		
1640	22.225	.8750	53.680	2.1	14.288	.5625	0.64	10000	5880		
1641	25.400	1	53.680	2.1	14.288	.5625	0.64	10000	5880		